



The Sol Series Cordex High-Performance switched mode rectifiers make a proven, reliable platform even better, with significant advancements in efficiency and performance. In a compact, fan-cooled design, Alpha's HP rectifiers open the possibility for immediate OPEX/CAPEX savings, reducing total cost of ownership and impact on the environment, and are useable under a wider range of applications.

The Sol Series Cordex HP 4.0kW is a perfect solution for various 48Vdc capacity applications from small remote sites to large power systems at CO's, MTSO's and Data centers. Unlike other rectifiers in its category, the Cordex HP 4.0kW provides 100% nominal power up to 55°C and at least 3600W up to 65°C. With a high operating efficiency (95.3%) and wide temperature operation (-40 to 75°C), HP series rectifiers are ideal for harsh outside plant enclosure installations.

The Sol Series Cordex HP 4.0kW is a backwards compatible solution with existing Cordex 3.6kW shelves and systems, providing users an easy upgrade path to greater power density and reduced OPEX.

Local and remote setup, adjustment and control is a simple single-step process with the Sol Series CXCI System Controller. By utilizing TCP/IP technology, complete configuration and monitoring of power equipment is possible through a network web browser.

- + High performance 83.3A rectifier for 48V telecom applications
- + 95.3% efficiency for increased OPEX savings and reduced carbon footprint
- + High power density 4RU compact design delivering up to 24kW per 23" shelf
- + Power limiting and wide range AC input for global installation requirements
- + Extended operating temperature range up to 75°C for deployment in the harshest outdoor environments
- + Backwards compatibility with the Sol Series Cordex 3.6kW rectifier shelves and power solutions providing cost effective upgrade path.

The Sol Series Cordex HP™ 4.0kW

Modular Switched Mode Rectifier

Electrical

Input voltage:	
Nominal:	208 to 277Vac
Operating:	187 to 312Vac
Extended:	187 to 90Vac (de-rated power)
Input frequency:	45 to 66Hz
Power factor:	>0.99 (50 to 100% load)
THD:	<5% (@ 208Vac)
Efficiency:	95.3%
Output voltage:	42 to 60Vdc
Output power:	4000W continuous
Float voltage:	48 to 58Vdc
Output current:	74A @ 54Vdc (83.3A max 48V)
Load regulation:	<±0.5% (static)
Line regulation:	<±0.1% (static)
Transient response:	±3% for 40 to 90% load step,
Noise:	
Voice band:	<38dBnC
Wide band:	<30mV RMS (10kHz to 10MHz)
	<150mV pk to pk (10kHz to 100MHz)
Psophometric:	<2mV
Acoustic:	<60dBa @ 1m (3ft)

Mechanical

Dimensions:	
mm:	160H x 87W x 300D
inches:	6.3H x 3.4W x 11.8D
Weight:	3.9kg (8.6lbs)

Performance/Features

Indicators:	AC mains OK — green LED
	Module OK — green LED
	Module fail — red LED
Controls:	CAN interface to CXC
Adjustments:	Float voltage
(via CXCI controller) ...	Equalize voltage
	High/low voltage alarm
	High voltage shutdown
	Current limit
	Slope
	Start delay
Protection:	Current limit/short circuit
	Start delay
	Input/output fuses
	Output high voltage shutdown
	Power limiting
	Thermal foldback/shutdown
	Input transient
	AC low line foldback/shutdown

Shelves

>Mechanical 19"/23" shelf (5 modules)

Dimensions:	
mm:	177H x 442W x 389D
inches:	6.9H x 17.4W x 15.3D
Weight:	8.5kg (19lbs)
Mounting:	Fits 19" rack flush/center mount
	Fits 23" rack center mount only

23" shelf (6 modules)

Dimensions:	
mm:	177H x 530W x 389D
inches:	6.9H x 20.8W x 15.3D
Weight:	9.5kg (21lbs)
Mounting:	Fits 23" racks only flush/center mount

Connections

Input:	Box type terminal block
	6 to 16mm ² (10 to 6AWG)
Output:	Bus adapters with 3/8" studs on 1" centers
Chassis ground:	Compression lug
	6 to 16mm ² (10 to 6AWG)
CAN communication: ..	RJ 12 offset

Environmental

Temperature:	
Operation:	-40 to 75°C (-40 to 176°F); full rated output
	up to 55°C (131°F); >3600W @ 65°C(149°F)
Storage:	-40 to 85°C (-40 to 185°F)
Humidity:	0 to 95% RH non-condensing
Elevation:	-500 to 4000m (-1640 to 13120ft)
Heat dissipation:	<1150 BTU per hour

Standards

Safety:	CSA C22.2 No 60950-1-03
	UL 60950-1
	CE Marked
	IEC/EN 60950-1
EMC:	ETSI 300 386
Emissions:	CFR47 (FCC) Part 15 Class B
	ICES-03 Class B
	EN55022 (CISPR 22) Class B
	C-Tick (Australia)
	EN 61000-3-2, 3-3
Immunity:	EN 61000-4-2, 4-3, 4-4, 4-5, 4-6, 4-11
	ANSI/IEEE C62.41 Cat B3
NEBS / Telcordia:	GR-1089-CORE
	GR-63-CORE

HELIOS
POWER SOLUTIONS

THE SOL SERIES

NEW ZEALAND

Phone: +64 9 835 0700
Email: sales@heliosps.co.nz
Address: 1 Heremai St,
Henderson, Auckland 0612

www.heliosps.co.nz

AUSTRALIA

Phone: +61 2 7200 9200
Email: sales@heliosps.com.au
Address: Unit 6, 2-8 South St,
Rydalmere, NSW 2116

www.heliosps.com.au

ASIA

Phone: +65 6871 4140
Email: sales@heliosps.asia
Address: 168 Robinson Road,
#12-01 Capital Tower, Singapore 048545

www.heliosps.asia